















DL-WP LED Wall Pack Light

Description

The Daylight WP series is a brilliant LED Wall Pack Luminaire that combines cutting egde optics and thermal management, with existing site aesthetics. These high performance wall mount fixtures distribute light like no others can, while providing unmatched energy saving of up to 80%. These lights are designed for quick and easy installation.

Characteristics

Optical: 120+ lm/Watt, 2700K-6000K, CRI >70

Electrical: 120-277V or 347-480V @ 700 mA, 80 to 240W models

available

Mechanical: Aluminum Housing, 10" x 6" x 4" powder coated Certifications/Ratings: cETLus, ROHS, IP65 rated. DLC Listed Reliability: "EncapsLED" heat sink for superior cooling and durability

(patent pending)

Warranty: 5 years (optional 10 years)

Options: 10KV Surge Protection (SP) Dimming (D) Photocell (PH)

Motion (M2) or Smart Control (MS)

Performance

Model(REG)	Wattage	5000K Lumens	Replaces MH/HPS Wattage	
DL-WP-10	10W	1,321	70W	
DL-WP-20	20W	2,640	100~150W	
DL-WP-30	30W	3,862	150~175W	
DL-WP-40	40W	4,980	175~250W	
DL-WP-50	50W	6,320	250~400W	
DL-WP-60	60W	7,533	400W	

Model(PR)	Wattage	5000K Lumens	Replaces MH/HPS Wattage	
DL-WP-10	10W	1,422	70W	
DL-WP-20	20W	2,708	100~150W	
DL-WP-30	30W	3,914	150~175W	
DL-WP-40	40W	5,082	175~250W	
DL-WP-50	50W	6,428	250~400W	
DL-WP-60	60W	7,712	400W	

Order Information

Example: DL-WP-20W-3M-5000K-BRN-PH-V1v

Model	Lens	Color Temp	Finish	Option	Voltage	Mounting
DL - WP - xxW	3M	2700k - 6000K	BRN –bronze WHT-white BLK-black SLV-Silver	0 - None SP - Surge Protection PH – Photon Cell M1 - Motion on/off M2 - Motion Mimming MS - Smart	V1 - 120 - 277VAC V2 - 347 - 480VAC	See Order Code